



05/06/2014

Declaration of Performance (DoP)

n° 000534002

1. Unique identification code of the product-type:

Sealants for non-structural use in joints in buildings. Sealants for facade elements

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4), of Reglement (UE) N° 305/2011

SEM MASTIC SILICONE NEUTRE BLANC

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer

One component sealant bases on silicone, neutral curing, sealant for external and internal, non structural use in facade joints, type F ext-int (25LM)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) of Reglement (UE) N° 305/2011

SEMIN SAS
1A RUE DE LA GARE
57920 KEDANGE SUR CANNER - France
Tél: +33 3 82 83 53 57
Fax: +33 3 82 83 93 33
mail@semin.com
www.semin.com

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of Reglement (UE) N° 305/2011

Not applicable.

6. System or systems of assessment and verification of constancy of performance of the onstruction as set out in Annex V of Reglement (UE) N° 305/2011

System 3

7. In the case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name and identification number of the notified body : GINGER CEBTP N°0074 and LNE N° 0071

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable.

9. Declared performance

| Commercial references | Essentials characteristics EN 15651-1:11/2012 | | | | | |
|----------------------------------|---|----------------------|--------------------------------|-----------------------------|--|------------|
| | Fire behaviour EN 13801:2007+A1:2009 | Dangerous substances | Resistance to flow EN ISO 7390 | Loss of volume EN ISO 10583 | Adhesion/cohesion properties after immersion into water EN ISO 10250 | Durability |
| SEM MASTIC SILICONE NEUTRE BLANC | E | assessed | ≤3mm | ≤10% | NF | conform |

NF= no failure according to EN ISO 11600

Pretreatment: method B; substrate: aluminium; without primer

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by : PHILIPPE SEMIN (PDG)

Place and date of issue : 05 JUIN 2014 à KEDANGE SUR CANNER

Signature :